

CF Series
Automated Butterfly Valves
Dimensions

2-WAY SERIES 41 HIGH PERFORMANCE VALVE WITH SERIES 70 ELECTRIC ACTUATOR

Valve NPT	Model No.	90° ¹	C _v 60° ²	A	B	C	D	E	Lug BC	Bolting Holes	Data Threads
2 1/2"	MKL2-x025	160	78	4.75	1.88	2.28	3.00	6.38	5.50	4	5/8-11
3"	MKL2-x030	185	123	5.25	1.88	2.86	3.25	6.63	6.00	4	5/8-11
4"	MKL2-x040	375	250	6.72	2.03	3.72	4.09	7.5	7.50	8	5/8-11
5"	MKL2-x050	790	360	7.62	2.23	4.83	5.07	7.5	8.50	8	3/4-10
6"	MKL2-x060	1350	510	8.62	2.23	5.88	5.57	8	9.50	8	3/4-10
8"	MKL2-x080	2800	1060	10.81	2.40	7.80	6.94	9.5	11.75	8	3/4-10
10"	MKL2-x100	4300	1630	13.06	2.75	9.78	8.56	10.75	14.25	12	7/8-9
12"	MKL2-x120	6650	2530	15.42	3.08	11.74	10.18	12.25	17.00	12	7/8-9

Actuator Model	F*	G	H
70-003/005	6.70	7.50	5.80
70-008/012/020	8.10	10.10	7.80
70-030/050/065	8.80	12.10	9.50

* Allow additional 5" for Actuator Cover removal.

